



**Whitham Mills**  
ENGINEERING

## BALING CONSUMABLES SPECIFICATION SHEET:

Product	Application	Ranges	Finishes/ Colours	Sizes	Key Features
<b>Steel wire</b>	Channel	Cut and loop	Black annealed (oiled)	UTS 340/432N/mm <sup>2</sup> (22-28Tsi)	Short leadtimes
	Twin Ram	Rewound coils	Black annealed (oiled)	UTS 494/590N/mm <sup>2</sup> (32-38Tsi)	UK production
	Semi Auto	Formers	Electro-galvanised		
<b>Wrap</b>	RDF/ SRF	Standard	Green, black, white	1500m x 750mm x 25 micron	Blown film for strength in every direction
	Cross Wrap	High density		1800m x 750mm x 22 micron	
	Tanco				
	McHale				
<b>Strap</b>	RDF/ SRF	High tension		16mm x 1mm x 1200m	Fully recyclable
		Green performance		16mm x 0.9mm x 1500m	Superior strength
<b>Plastic wire</b>	RDF/ SRF	40kg	On reels	4mm thickness, 1900m	In stock
		270kg		4mm thickness, 13000m	



**Whitham Mills Engineering Limited**  
Unit 70 Whitbrook Way,  
Stakehill Industrial Estate,  
Manchester,  
M24 2SS



(+44) 01706 811880



Sales@whithammills.com  
Service@whithammills.com  
Projects@whithammills.com